

RUBIA XRI 10W-40



DAF TRUCKS Factory Fill - EXTENDED ENGINE OIL

APPLICATIONS

A “**made for DAF**” product, specially developed for new generation of heavy duty engines. Used by DAF for factory fill on Euro III engines and after-market applications.

PERFORMANCES

Meets and exceeds the following international specifications :

- ✓ **API CI-4**
- ✓ **ACEA E7**

Approved by **DAF TRUCKS NV** on Euro III engines as a result of :

- ✓ extensive fleet testing over 2,6 millions of kilometers under extreme conditions to guarantee reliability and exceptional lubrication properties such as piston cleanliness and thermal stability
- ✓ In-house engine testing by DAF Trucks to evaluate running-in performance, anti-wear properties and ability to maintain engine cleanliness even with a high soot content.

CUSTOMER BENEFITS

- ✓ Reliability due to its **approved part status** : optimize engine lifetime
- ✓ Enables longer drain intervals while conserving its very high performances
- ✓ Ensure a proper « running-in » period and an after-market utilisation due to it's innovating **dual formulation technology**
- ✓ Helps minimizing the oil consumption losses as a result of it's viscosymetric properties

CHARACTERISTICS

RUBIA XRI 10W-40	Units	SAE 10W-40
Density	kg/m ³	873
Viscosity at 100°C	mm ² /s	14
Flash point	°C	> 200
Base Number	mgKOH/g	10.5

TOTAL LUBRIFIANTS
16, rue de la République
F- 92800 PUTEAUX
1/2

RUBIA XRI SAE 10W-40
07/12/2005
N° MPR 12/05



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.



TOTAL

Pour Point	°C	-36
------------	----	-----

The typical characteristics mentioned represent mean values

