

LUBRILAM S 30 L



Metalworking



Base oil for rolling.

UTILISATIONS

- Aluminium rolling non staining base stock.

ADVANTAGES

- Very low aromatic (0,03%) and sulfur content.
- High thermal and UV resistance.
- Narrow cut allowing processing cost reductions.

TYPICAL CHARACTERISTICS	METHODS	UNITS	LUBRILAM S 30 L
Density at 15°C	NFT 60172	kg/m ³	802
Colour	NFM 07003	-	+ 30 mini.
Distillation :	NFM 07002		
Initial point		°C	> 220
Dry point		°C	< 240
Flash point	NFM 07019	°C	92
Pour point	NFT 60105	°C	- 45
Aromatics content	UV	% mass	0,03 maxi.
Viscosity at 20 °C	ISO 3104	mm ² /s	2.7
Viscosity at 40 °C	ISO 3104	mm ² /s	1.9
Benzene content	ASTM D 4367	ppm	1 maxi.
Aniline point	NFM 07021	°C	76
Sulfur content	ASTM D 3120	ppm	1 maxi.

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS

Industrie & Spécialités

21 july 2003 (supersedes 7 september 2001)

LUBRILAM S 30 L

1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from

www.quick-fds.com.

