

MARTOL EV 5Y13



DRAWING

Special fluid for aluminium drawing and shearing and to be used as detaching agent for aluminium sheets to be painted.

DESCRIPTION

- **Martol EV 5Y13** is a special evaporable drawing product suitable for drawing or shearing of tin aluminium
- **It is specially studied to be usefull as detaching agent for aluminium sheets to paint, without interference in the hardness of the paint.**

APPLICATIONS

- **MARTOL EV 5Y13** is particulary studied because:
 - the solvent base is easy evaporable
 - the solvent base is with a very low smell.
 - the active matter is non-oxidable and so without unpleasant smells also with a long stocking time
 - **the active matter doesn't interfere with the hardness of the paint, without removal of the detaching agent**
- **MARTOL EV 5Y13** assures
 - good lubricating properties
 - excellent antiweld properties
 - good evaporation rate

Typical Characteristics

Test methods	Determinations	MARTOL EV 5Y13
Interne	Appearance	Clear
Interne	Colour	Colourless
ASTM D-4052	Density at 20°C	0,771
ASTM D-445	Viscosity at 40°C	1,40
ASTM D-445	Viscosity at 20°C	1,90
ASTM D-92	Flash point P.M.	72

Above characteristics are mean values given as an information.