

RUBIA TDI

15W-40



Multigrade oil for diesel engine

UTILISATION

- Specially developed for lubrication of turbocharged and not, Euro 1, Diesel engines.
- Suitable for all Diesel engines in severe service conditions.
- Suited for extended drain intervals (up to 30 000 km according to manufacturers).
- Suited for engines of earth moving machinery which need an API CF-4 level lubricant.

PERFORMANCES

Specifications

API MIL-L CF-4/SG 2104D

Level

VOLVO VDS

CUSTOMER BENEFITS

Performances techniques

- Multigrade
- Very high viscosity index
- Excellent viscosity stability
- Excellent detergency level
- Very high dispersancy level
- Excellent antiwear, anticorrosion and antifoam properties

CHARACTERISTICS

	Units	SAE grade 15W-40
Volumetric mass at 15°C	kg/m ³	885
Viscosity at 100°C	mm ² /s	14,2
Viscosity index	-	135
Flash Point	°C	225
Pour point	°C	-30
T.B.N	mgKOH/g	8,2

The typical characteristics mentioned represent mean values.

TOTAL ITALIA SPA

Via Arconati, 1
20135 Milano (MI)
ITALY

RUBIA TDI 15W-40
01/05/2004



This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.